



STIGMA-ROTARY

THE STIGMA®- ROTARY TATTOO MACHINES WERE DEVELOPED/DESIGNED BY EXPERIENCED TATTOO ARTIST ARTEMIS ROSAKIS WHICH DID NOT FOUND THE PERFECT MACHINE TO WORK WITH AND DECIDED TO BUILD SUCH. THE CREATION IS COMBINING THE BENEFITS OF A COIL MACHINE (SOFTNESS/ADJUSTMENTS) WITH THE USE OF A ROTARY MACHINE (LESS VIBRATIONS/LESS NOISE/NO TUNING). THE TECHNOLOGY BEHIND STIGMA® MACHINES SAVES YOU A LOT OF PRE-TATTOOING TIME (ADJUSTMENTS & TUNING TIME) IT ALSO HELPS YOU TO COMPLETE YOUR WORK FASTER AND EASIER. IT IS NOT JUST EASIER & FASTER WORKING - IT IS ALSO BETTER FOR YOUR HEALTH (LESS VIBRATION, LESS WEIGHT AND LESS NOISE).

STIGMA® "HYPER" TATTOO MACHINE

SEMI ROTARY TATTOO MACHINE WITH SWASH-PLATE TECHNOLOGY AND VERTICALLY PLACED MOTOR. PLACING THE MOTOR VERTICALLY IS BRINGING THE WEIGHT-CENTER POINT OF THE MACHINE CLOSER TO YOUR FINGERS. YOUR DIRECT BENEFIT IS A BETTER BALANCED MACHINE AND LESS TIREDNESS OF YOUR FINGERS.

THE HARDNESS/SOFTNESS OF THE "STROKE/PUNCH" IS ADJUSTABLE. BY SIMPLY TURNING THE CONTROL-THUMBSCREW YOU CAN TURN THE "HYPER" MACHINE FROM HARD HITTING (LINER) TO SOFT HITTING (SHADER). THIS ADJUSTMENT IS FOUND ONLY ON THE STIGMA®- ROTARIES AND IS SOLVING THE OLD PROBLEMS OF USING ROTARIES WITHOUT ANY CONTROL ON THE HARDNESS /SOFTNESS.

THE MACHINE PARTS ARE PRODUCED TO PRECISION IN GERMANY. THE FRAME IS CNC MACHINED FROM A SOLID BLOCK OF AIRCRAFT ALUMINIUM AND THEN DEEP ANODIZED. ROBUST FRAME AND HI-TECH CONSTRUCTION.

THE WEIGHT OF THE "HYPER" MACHINE IS 115gr/4oz. THE "HYPER" MACHINE CAN BE USED WITH RCA OR STANDARD CLIPCORD. SWISS MADE POWERFULL (4.5watt) MOTOR.

USE OF STANDARD NEEDLES AND STANDARD BACK TUBE. CAN BE USED WITH ALMOST EVERY POWER-SUPPLY.

THE WORKING VOLTAGE RANGE IS 7-12volt DC (**NEVER TO BE USE WITH MORE THEN 12volt!!!**). THE HYPER MACHINE HAS POLARITY PROTECTION (TURN CLIPCORD IF MACHINE IS CONNECTED BUT NOT WORKING).

WHEN THE MACHINE IS STOPS WORKING THE NEEDLES ARE ALWAYS PUSHED UP (OUT OF THE SKIN/INTO THE TIP).

PATENT-PENDING MACHINE AND COPYRIGHT PROTECTED DESIGN. WE WILL FIGHT EVERY COPY/IMITATION (NOT JUST PRODUCERS BUT ALSO RE-SELLERS) !!!

For ordering – visit www.coldskin.nl (contact stigma@coldskin.nl)

For service – contact info@stigma-rotary-tattoo.com

For use advice/experience – contact info@magic-tattoo.com

VERY IMPORTANT

USE ONLY SYNTHETIC GREASE
TO LUBRICATE THE MACHINE

DO NOT LUBRICATE THE SWASH-PLATE
OR THE MOTOR

THIS MACHINE WILL RUN ONLY IF THE
POLARITY ON THE WIRES IS CORRECT
IF YOUR MACHINE DOES NOT RUN BY
THE CLIPCORD THEN REVERSE THE
CLIPCORD

IF YOUR MACHINE DOES NOT RUN
BY THE RCA THEN SWITCH THE
WIRES ON YOUR POWER SUPPLY
OR ON THE RCA CORD

RUN BETWEEN 7 ~ 12 VOLTS
BEST IS 8 ~ 11 VOLTS

MAXIMUM 12 VOLTS

USE THE CONTROL - THUMBSCREW
TO CONTROL SENSITIVITY (GIVE)

YOU CAN ADJUST THE THUMBSCREW WITH
YOUR FINGERS OR WITH AN ALLEN KEY (HEX)
THEN RUN THE MACHINE AND TOUCH THE
NEEDLE BAR TO TEST THE SENSITIVITY

DO NOT REMOVE THE CONTROL SCREW
COMPLETELY OUT OF THE MACHINE
UNSCREW IT MAXIMUM 2 TIMES
360 DEGREE

TIGHT FOR LINING
LOOSE FOR SHADING



LUBRICATE THE MOVING
ARMATURE HOUSING
RIGHT THERE WITH
SYNTHETIC GREASE
EVERY ABOUT 30 ~ 50
OPERATING HOURS

FOR SERVICE CONTACT

www.stigma-rotary-tattoo.com

www.magic-tattoo.com

info@stigma-rotary-tattoo.com

info@magic-tattoo.com

STIGMA-ROTARY